

Zerex® HD EXTENDED LIFE RTU
ANTIFREEZE COOLANT ZXEDRU1

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)

Product name	Zerex® HD EXTENDED LIFE RTU ANTIFREEZE COOLANT
Product code	ZXEDRU1
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, dark orange

WARNING! MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. HARMFUL IF SWALLOWED. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN AND RESPIRATORY TRACT IRRITATION.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin contact

Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Although rare, skin contact with ethylene glycol may cause allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects).

Ingestion

Zerex® HD EXTENDED LIFE RTU
ANTIFREEZE COOLANT ZXEDRU1

Swallowing this material may be harmful. Liver, kidney and brain damage in humans has resulted from swallowing lethal or near-lethal amounts of ethylene glycol. Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in humans. Products containing diethylene glycol should be considered toxic by ingestion.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Upper respiratory tract, Skin, lung (for example, asthma-like conditions), Liver, kidney, Exposure to this material may aggravate any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), Cough, central nervous system excitation (giddiness, liveliness, light-headed feeling) followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, involuntary eye movement, chest pain, cyanosis (causes blue coloring of the skin and nails from lack of oxygen), lung edema (fluid buildup in the lung tissue), acute kidney failure (sudden slowing or stopping of urine production), liver damage, Convulsions, damage to the mouth, throat, and/or airways, lung damage, coma

Target Organs

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: reproductive effects, effects on male fertility, kidney damage, liver abnormalities, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: kidney damage, liver damage

Carcinogenicity

Zerex® HD EXTENDED LIFE RTU
ANTIFREEZE COOLANT ZXEDRU1

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

Ethylene glycol has caused birth defects in animal studies at high oral doses. However, it did not cause harm to the pregnant animal or to the fetus when applied to the skin of the pregnant animal., 2-Ethylhexanoic acid has been shown to cause birth defects in laboratory animal studies. The relevance of these findings to humans is uncertain.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
ETHYLENE GLYCOL	107-21-1	>=40-<50%
DIETHYLENE GLYCOL	111-46-6	>=1.5-<5%
2-ETHYLHEXANOIC ACID	149-57-5	>=1.5-<5%
POTASSIUM HYDROXIDE	1310-58-3	>=1.5-<5%

4. FIRST AID MEASURES**Eyes**

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention. Do not remove the victim from water access for transport to a medical facility unless instructed to do so by qualified medical personnel. If possible, continue flushing the eye gently with water while transporting the victim.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Zerex® HD EXTENDED LIFE RTU
ANTIFREEZE COOLANT ZXEDRU1

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.

Treatment: This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water spray, Carbon dioxide (CO₂), Dry chemical

Hazardous combustion products

Alcohols, Aldehydes, carbon dioxide and carbon monoxide, Hydrocarbons, ethers, toxic fumes

Precautions for fire-fighting

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full

Zerex® HD EXTENDED LIFE RTU
ANTIFREEZE COOLANT ZXEDRU1

Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

Flammability Class for Flammable Liquids
Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Keep containers closed when not in use. Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Zerex® HD EXTENDED LIFE RTU
ANTIFREEZE COOLANT ZXEDRU1

Exposure Guidelines

ETHYLENE GLYCOL		107-21-1	
ACGIH	Ceiling Limit Value:	100 mg/m3	Aerosol.
2-ETHYLHEXANOIC ACID		149-57-5	
ACGIH	time weighted average	5 mg/m3	Inhalable fraction and vapor
POTASSIUM HYDROXIDE		1310-58-3	
ACGIH	Ceiling Limit Value:	2 mg/m3	
NIOSH	Recommended exposure limit (REL):	2 mg/m3	

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product. Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory protection

Zerex® HD EXTENDED LIFE RTU
ANTIFREEZE COOLANT ZXEDRU1

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	dark orange
Odour	No data
Boiling point/boiling range	107.00 °C / 225 °F
Melting point/range	-33 °F / -36 °C
pH	(+/- 0.7) 8.7
Flash point	(>)250 °F / 121 °C
Evaporation rate	No data
Explosion limits	1 %(V) 15.3 %(V)
Vapour pressure	23.33 hPa @ 68 °F / 20 °C
Vapour density	No data
Density	(Average) 1.075 g/cm ³ @ 60.1 °F / 15.6 °C 8.93 lb/gal @ 60.1 °F / 15.6 °C
Solubility	No data
Partition coefficient: n-octanol/water	No data
log Pow	no data available
Autoignition temperature	No data

10. STABILITY AND REACTIVITY**Stability**
Stable.**Conditions to avoid**
None known.**Incompatible products**

Zerex® HD EXTENDED LIFE RTU
ANTIFREEZE COOLANT ZXEDRU1

Acids, Alkaline earth metals, Alkali metals, Amines, Ammonia, chlorinated solvents, halogenated hydrocarbons, Reducing agents, strong alkalis, Strong oxidizing agents, Sulphur compounds, Zinc

Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

ETHYLENE GLYCOL	LD 50 Rat: 6,140 mg/kg
DIETHYLENE GLYCOL	LD 50 Rat: 12,565 mg/kg
2-ETHYLHEXANOIC ACID	LD 50 Rat: 3 g/kg
POTASSIUM HYDROXIDE	LD 50 Rat: 1,230 mg/kg

Acute inhalation toxicity

ETHYLENE GLYCOL	no data available
DIETHYLENE GLYCOL	LC Lo Mouse: 130 mg/m ³ , 2 h
2-ETHYLHEXANOIC ACID	LC 50 Rat: > 600 ppm, 4 h
POTASSIUM HYDROXIDE	no data available

Acute dermal toxicity

ETHYLENE GLYCOL	LD 50 Rabbit: 9,530 mg/kg
DIETHYLENE GLYCOL	LD 50 Rabbit: 11,890 mg/kg
2-ETHYLHEXANOIC ACID	LD 50 Rabbit: 1,138 mg/kg
POTASSIUM HYDROXIDE	LD 50 Rabbit: 1,260 mg/kg

Zerex® HD EXTENDED LIFE RTU
ANTIFREEZE COOLANT ZXEDRU1

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental fate and pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification Acute Health Hazard

SARA 313 Component(s)

ETHYLENE GLYCOL	107-21-1	48.72%
-----------------	----------	--------

Zerex® HD EXTENDED LIFE RTU
ANTIFREEZE COOLANT ZXEDRU1

New Jersey RTK Label Information

ETHYLENE GLYCOL	107-21-1
WATER	7732-18-5
DIETHYLENE GLYCOL	111-46-6
2-ETHYLHEXANOIC ACID	149-57-5
POTASSIUM HYDROXIDE	1310-58-3

Pennsylvania RTK Label Information

ETHYLENE GLYCOL	107-21-1
WATER	7732-18-5
DIETHYLENE GLYCOL	111-46-6
POTASSIUM HYDROXIDE	1310-58-3

Reportable quantity - Product

US. EPA CERCLA Hazardous Substances (40 CFR 302)	10262 lbs
--	-----------

Reportable quantity - Components

ETHYLENE GLYCOL	107-21-1	5000 lbs
DIETHYLENE GLYCOL	111-46-6	none
2-ETHYLHEXANOIC ACID	149-57-5	none
POTASSIUM HYDROXIDE	1310-58-3	1000 lbs

	Health	Flammability	Reactivity	Other
HMIS	2*	1	0	
NFPA	1	1	0	

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).