


1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	RED LINE DIESEL FUEL CATALYST & CATALYST WINTERIZED
1.2	Chemical Name:	Diesel Fuel Mixture
1.3	Synonyms:	NA
1.4	Trade Names:	Red Line Diesel Fuel Catalyst & Catalyst Winterized
1.5	Product Use:	Fuel System Cleaner, Improve Diesel Fuel Combustion
1.6	Distributor's Name:	Worldpac, Inc.
1.7	Distributor's Address:	37137 Hickory Street, Newark, CA 94560 USA
1.8	Emergency Phone:	INFOTRAC: +1 (800) 535-5053 / +1 (352) 323-3500 (CONTRACT 84261)
1.9	Business Phone / Fax:	+1 (510) 608-5525 / +1 (510) 742-9262

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a hazardous substance but not as dangerous goods according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).</p> <p>DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAY. MAY CAUSE AN ALLERGIC SKIN REACTION.</p> <p><u>Hazard Statements</u> (H): H304 – May be fatal if swallowed and enters airways. H317 – May cause an allergic skin reaction.</p> <p><u>Precautionary Statements</u> (P): P280 – Wear protective gloves/eye protection. P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301 - Do NOT induce vomiting. P261 - Avoid breathing mist/sprays. P272 – Contaminated work clothing should not be allowed out of the workplace. P302+P352 – IF ON SKIN: Wash with plenty of soap and water. P333+P313 – If skin irritation or rash occurs: Get medical advice/attention. P321 – For specific treatment – see section 4 of this Safety Data Sheet. P363 Wash contaminated clothing before reuse. P405 – Store locked up. P501 - Dispose of contents/container to licenses treatment, storage and disposal facility (TSDF).</p>	
2.2	Effects of Exposure:	<p><u>Eyes</u>: May cause irritation, redness and tearing. Vapors may be irritating to the eyes. Risk of conjunctivitis.</p> <p><u>Skin</u>: May cause irritation, defatting, drying and cracking of skin. Prolonged and repeated contact may lead to dermatitis.</p> <p><u>Ingestion</u>: May cause a burning sensation of the mouth and throat, abdominal pain, gastrointestinal irritation, nausea, vomiting and diarrhea. May also cause kidney damage, cardiac arrhythmia and Central Nervous System effects (see inhalation). Aspiration of material into the lungs may cause chemical pneumonitis, which can be fatal. Can be fatal if inhaled or ingested.</p> <p><u>Inhalation</u>: Vapors may be irritating to nose, throat and respiratory tract. Excessive inhalation of vapors may cause kidney damage, cardiac arrhythmia and Central Nervous System effects including dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.</p>	
2.3	Symptoms of Overexposure:	<p><u>Eyes</u>: Irritation, redness, swelling and tearing.</p> <p><u>Skin</u>: Irritation, defatting, drying and cracking of skin.</p> <p><u>Ingestion</u>: Burning sensation of the mouth and throat, abdominal pain, gastrointestinal irritation, nausea, vomiting and diarrhea.</p> <p><u>Inhalation</u>: Irritation to nose, throat and respiratory tract, dizziness, coughing, wheezing, weakness, fatigue, nausea, headache and possible unconsciousness.</p>	
2.4	Acute Health Effects:	Moderate irritation to eyes. Moderate irritation to skin near affected areas. Vapors may be irritating to nose, throat and respiratory tract.	
2.5	Chronic Health Effects:	Prolonged or repeated skin contact may lead to dermatitis. <u>Xylene</u> has been found to cause cardiac, liver, and kidney effects, anemia and eye damage in laboratory animals.	
2.6	Target Organs:	Lungs, upper respiratory tract, liver, kidneys, skin.	

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)								
					ACGIH		NOHSC			OSHA			OTHER
					TLV	STEL	ppm	ppm	ppm	ppm	ppm	ppm	
SOLVENT NAPHTHA	64742-88-7	WJ8930000	265-191-7	60-100	NA	NA	NF	NF	NF	NA	NA	NA	
	Asp. Tox. 1; H304												
SOLVENT NAPHTHA	64742-95-6	WF3400000	265-199-0	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
	Carc. 1B; Muta. 1B; Asp. Tox. 1; H350, H340, H304												
1,2,4-TRIMETHYLBENZENE	95-63-6	DC3325000	202-436-9	0.1-1	25	NA	25	NF	NF	NA	NA	NA	25 NIOSH
	Flam. Liq. 3; Acute Tox. 4*; Eye Irrit. 2; STOT SE 3; Skin Irrit. 2; Aquatic Chronic 2; H226, H332, H319, H335, H315, H411												


NA = Not Available; ND = Not Determined; NE = Not Established; NF = Not Found; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used
 NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2010 format.

4. FIRST AID MEASURES

4.1	First Aid:	<p>Ingestion: Do NOT induce vomiting. Contact Infotrac +1 (800) 535-5053 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.</p> <p>Eyes: If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.</p> <p>Skin: Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned.</p> <p>Inhalation: Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial respiration. Seek immediate medical attention.</p>										
4.2	Medical Conditions Aggravated by Exposure:	Persons with pre-existing skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.										
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: #0000FF; color: white;">HEALTH</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: #FF0000; color: white;">FLAMMABILITY</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: #FFA500; color: white;">PHYSICAL HAZARDS</td> <td style="text-align: center;">0</td> </tr> <tr> <td colspan="2" style="background-color: #000000; color: white;">PROTECTIVE EQUIPMENT</td> </tr> <tr> <td style="background-color: #000000; color: white;">EYES</td> <td style="background-color: #000000; color: white;">SKIN</td> </tr> </table>	HEALTH	2	FLAMMABILITY	2	PHYSICAL HAZARDS	0	PROTECTIVE EQUIPMENT		EYES	SKIN
HEALTH	2											
FLAMMABILITY	2											
PHYSICAL HAZARDS	0											
PROTECTIVE EQUIPMENT												
EYES	SKIN											

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	Wear suitable protective clothing and gloves. Wear eye/face protection. This material can burn but will not readily ignite. This material will release vapors when heated above the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point. Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulfur and nitrogen. Also, depending upon the conditions of use, low concentrations of hydrogen sulfide can be released.
5.2	Extinguishing Methods:	Water, Foam, CO ₂ , Dry Chemical, low velocity water fog, Halon (if permitted),
5.3	Firefighting Procedures:	As with any fire, firefighters should wear appropriate protective equipment including a MSHA/NIOSH approved or equivalent self-contained breathing apparatus (SCBA) and protective clothing. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.





6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE). Use safety glasses or safety goggles and face shield; use gloves and other protective clothing (e.g., apron, boots, etc.) to prevent skin contact. Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible, inert material such as vermiculite or sand to soak up the product and place into a container for later disposal. Large Spills: Keep incompatible materials (e.g., oxidizers, strong acids, alkalis) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Recover as much free liquid as possible and collect in acid-resistant container. Use absorbent to pick up residue. Avoid discharging liquid directly into a sewer or surface waters.
-----	---------	--

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid breathing mists or spray. Avoid eye and skin contact. Wear protective equipment when handling product. Keep out of the reach of children. Do not eat, drink or smoke when handling this product. Wash thoroughly after handling. Do not expose to heat and flame. Use only in ventilated areas. Immediately clean-up and decontaminate any spills or residues.
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Store in closed containers. Avoid temperatures above 40°C (120°F). Keep away from incompatible substances (see Section 10). Protect containers from physical damage.
7.3	Special Precautions:	Empty containers may retain hazardous product residues.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Ventilation & Engineering Controls:	Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).	
8.2	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.	
8.3	Eye Protection:	Avoid eye contact. Safety glasses with side shields must be used when handling or using this product. A protective face shield is also recommended. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU).	
8.4	Hand Protection:	Wear protective, chemical-resistant gloves (e.g., neoprene, nitrile, PVC) when using or handling this product. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product.	
8.5	Body Protection:	Not required under normal conditions of use. A chemical resistant apron and/or protective clothing are recommended when handling or using large quantities (e.g., > 5 gallons (18.9 L)) of this product. Protective working garments should meet EU Standard EN 344 or equivalent.	

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Reddish-brown liquid
9.2	Odor:	Strong petroleum odor
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	NA
9.7	Flashpoint:	82 °C (180 °F)
9.8	Upper/Lower Flammability Limits:	LEL: 0.7%, UEL: 6.0%
9.9	Vapor Pressure:	< 1.0 mm Hg @ 20 °C (68 °F)
9.10	Vapor Density:	NA
9.11	Relative Density:	0.9 g/cm ³
9.12	Solubility:	Insoluble
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	235-315°C (455-599 °F), ASTM E-659
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	Kinematic @ 40 °C (104 °F): > 13 mm ² /s
9.17	Other Information:	NA

10. STABILITY & REACTIVITY

10.1	Stability:	This product is stable under normal storage and use conditions.
10.2	Hazardous Decomposition Products:	Oxides of carbon (CO, CO ₂), sulfur (SO _x), and nitrogen (NO _x).
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Open flames, high heat and direct sunlight.
10.5	Incompatible Substances:	Strong oxidizing agents, acids or alkalis.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: NO	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has not been tested on animals to obtain toxicological data. Toxicology data for some of the components in this mixture, found in scientific literature, are presented below: Xylene: LD ₅₀ (oral, rat): 5000 mg/kg.		
11.3	Acute Toxicity:	See section 2.4.		
11.4	Chronic Toxicity:	See section 2.5		
11.5	Suspected Carcinogen:	ACGIH: A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans (listed under Diesel Fuel)		
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenicity effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	See Section 2.3		
11.8	Biological Exposure Indices:	NA		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	Keep out of sewers, drainage areas and waterways. Report spills and releases, as applicable, under Federal and State regulations.
12.2	Effects on Plants & Animals:	An environmental fate analysis has not been conducted on this specific product. However, plants and animals may experience harmful or fatal effects when coated with petroleum-based products.
12.3	Effects on Aquatic Life:	Diesel Fuel: LC ₅₀ (Pimephales promelas (fish), 96h): 35 mg/L; EC ₅₀ (Daphnia magna, 48h): 1.96 mg/L

13. DISPOSAL CONSIDERATIONS



13.1	Waste Disposal:	Dispose of in accordance with federal, state, provincial and local regulations.
13.2	Special Considerations:	If disposed of, this material is believed to be a hazardous waste under RCRA due to toxicity. Waste management should be in compliance with federal, state, and local laws. If discarding this material, consider the possible relevance of the following chemicals and the treatment standards for the associated. U.S. EPA RCRA Hazardous Waste Codes (HWC): D018 (Benzene); F003 (Xylene)

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADGT, ADR and the CTDGR.

14.1	49 CFR (GND):	NA1993, COMBUSTIBLE LIQUIDS, N.O.S., 3, III Excepted from regulation per 49 CFR §173.121, IP VOL ≤ 450 L.
14.2	IATA (AIR):	NOT REGULATED
14.3	IMDG (OCN):	NOT REGULATED
14.4	TDGR (Canadian GND):	NOT REGULATED
14.5	ADR/RID (EU):	NOT REGULATED
14.6	SCT (MEXICO):	NOT REGULATED
14.7	ADGR (AUS):	NOT REGULATED

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product contains <u>Xylene</u> , a substance subject to Section 313 reporting requirements.
15.2	SARA Threshold Planning Quantity:	NA
15.3	TSCA Inventory Status:	All components of this product are listed in the TSCA Inventory or are exempt.
15.4	CERCLA Reportable Quantity (RQ):	<u>Xylene</u> : 100 lbs (45.4 kg)
15.5	Other Federal Requirements:	NA
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS D2B (Other Toxic Effects). 
15.7	State Regulatory Information:	<u>Xylene</u> is found on the following state criteria list Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). This product may contain slight but detectable amounts of a chemical known to the State of California to cause cancer (Benzene). No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).
15.8	Other Requirements:	The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC. <u>Solvent Naphtha</u> : Harmful (Xn). <u>Risk Phrases</u> (R): R65 – Harmful: may cause lung damage if swallowed. <u>Safety Phrases</u> (S): (2-)23-24-62 - Keep out of the reach of children. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label where possible. 

16. OTHER INFORMATION

16.1	Other Information:	<p>DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAY. May cause an allergic skin reaction. Wear protective gloves/eye protection. If swallowed, immediately call a Poison Center or doctor/physician. Avoid breathing mist/sprays. If skin irritation or rash occurs: Get medical advice/attention. KEEP OUT OF REACH OF CHILDREN.</p>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	<p>This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Worldpac's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.</p>	
16.4	Prepared for:	<p>Worldpac, Inc. 37137 Hickory Street Newark, CA 94560 USA Tel: +1 (510) 608-5525 Fax: +1 (510) 742-9262 http://www.worldpac.com</p>	
16.5	Prepared by:	<p>ShipMate, Inc. P.O. Box 787 Sisters, OR 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com</p>	

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
----------------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A	
B	
C	
D	
E	
F	

G	
H	
I	
J	
K	
X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₀₁	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₀₁, LD₀₁, & LD₀₂ or TC, TC₀₁, LC₀₁, & LC₀₂	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment