



# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2015

Version 4

Reviewed on 05/30/2015

## 1 Identification

### Product identifier

**Trade name:** Original ATE Brake Fluid TYP 200 (DOT 4)

**Article number:** 03.9901-62xx.x / 7062xx

### Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

**Application of the substance / the mixture** hydraulic liquid

### Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

Continental Aftermarket GmbH

Guerickestr. 7

60488 Frankfurt a. M.

Germany

Tel: +49-69-76031

Fax: +49-69-761061

#### Information department:

Gefahrstoffmanagement Konzern, Zentrales Materiallabor

ate.sicherheit@contiautomotive.com

**Emergency telephone number:** +49-6132-84463

## 2 Hazard(s) identification

### Classification of the substance or mixture



Health hazard

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

### Label elements

#### GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

**Hazard pictograms** GHS08

**Signal word** Warning

#### Hazard-determining components of labeling:

2,2'-oxybisethanol

#### Hazard statements

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

#### Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Get medical advice/attention if you feel unwell.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Classification system:

#### NFPA ratings (scale 0 - 4)



Health = 0

Fire = 1

Reactivity = 0

#### HMIS-ratings (scale 0 - 4)



Health = 1

Fire = 1

Reactivity = 0

(Contd. on page 2)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2015

Version 4

Reviewed on 05/30/2015

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

(Contd. of page 1)

**Other hazards****Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

### 3 Composition/information on ingredients

**Chemical characterization: Mixtures****Description:** Mixture of the substances listed below with nonhazardous additions.**Dangerous components:**

15520-05-5	2,2'-(Octylimino)bisethanol ⚠ Acute Tox. 3, H301; ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315	<5%
111-46-6	2,2'-oxybisethanol ⚠ STOT RE 2, H373; ⚠ Acute Tox. 4, H302	<5%

### 4 First-aid measures

**Description of first aid measures****General information:** Remove contaminated clothes and shoes immediately.**After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** Call a doctor immediately.**Information for doctor:****Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

**Extinguishing media****Suitable extinguishing agents:**CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

**Special hazards arising from the substance or mixture**May be released in case of fire: CO, CO<sub>2</sub>, NO<sub>x</sub>**Advice for firefighters****Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

### 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

**Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

**Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)



# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/05/2015

Version 4

Reviewed on 05/30/2015

**Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)**

(Contd. of page 2)

Dispose of the collected material according to regulations.

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

**Handling:**

**Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

**Information about protection against explosions and fires:** No special measures required.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** Storage at room temperature.

**Information about storage in one common storage facility:** Store away from foodstuffs.

**Further information about storage conditions:**

Store in dry conditions.

This product is hygroscopic.

Keep receptacle tightly sealed.

**Storage class:** 10 combustible liquids.

**Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

**Additional information about design of technical systems:** No further data; see item 7.

**Control parameters**

**Components with limit values that require monitoring at the workplace:**

111-46-6 2,2'-oxybisethanol

WEEL	Long-term value: 10 mg/m <sup>3</sup>
------	---------------------------------------

**Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

**Breathing equipment:**

If occupational exposure limits are exceeded, use breathing mask (filter type A). Wear self-contained breathing apparatus in case of danger of oxygen displacement.

**Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

**Penetration time of glove material**

Butyl caoutchouc (butyl rubber): minimum breakthrough times 180 min; minimum layer thickness: 0.7 mm

NBR (nitrile rubber): minimum breakthrough times 30 min; minimum layer thickness: 0.4 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:** Safety glasses

(Contd. on page 4)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2015

Version 4

Reviewed on 05/30/2015

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

**Limitation and supervision of exposure into the environment**  
See section 6 and 7. No additional measures necessary.

(Contd. of page 3)

## 9 Physical and chemical properties

### Information on basic physical and chemical properties

#### General Information

#### Appearance:

Form:	Fluid
Color:	Light yellow
Odor:	Characteristic
Odour threshold:	Not determined.

pH-value at 20 °C (68 °F): 7-8 (FMVSS 116)

#### Change in condition

Melting point/Melting range:	< -70 °C (< -94 °F) (DIN 51583)
Boiling point/Boiling range:	> 280 °C (> 536 °F) (FMVSS 116)

Flash point: > 130 °C (> 266 °F) (ISO 2592 (open cup))

Flammability (solid, gaseous): Not applicable.

Ignition temperature: > 200 °C (> 392 °F) (DIN 51794)

Decomposition temperature: 360 °C (680 °F) (Analogy)

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

#### Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

Vapor pressure at 20 °C (68 °F): < 0.1 mbar

Density at 20 °C (68 °F): 1.08 g/cm<sup>3</sup> (9.013 lbs/gal) (DIN 51757)

Relative density: Not determined.

Vapour density: Not determined.

Evaporation rate: Not determined.

Water at 20 °C (68 °F): 350 g/l

Partition coefficient (n-octanol/water): Not determined.

#### Viscosity:

Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	17.5 mm <sup>2</sup> /s

#### Solvent content:

Organic solvents: 2.0 %

VOC content: 2.0 %

Other information: No further relevant information available.

## 10 Stability and reactivity

### Reactivity

#### Chemical stability

#### Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

**Possibility of hazardous reactions** No dangerous reactions known.

**Conditions to avoid** No further relevant information available.

(Contd. on page 5)



# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/05/2015

Version 4

Reviewed on 05/30/2015

**Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)**

(Contd. of page 4)

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

#### Information on toxicological effects

##### Acute toxicity:

##### LD/LC50 values that are relevant for classification:

Oral	LD50	>2000 mg/kg (-)
------	------	-----------------

##### Primary irritant effect:

**on the skin:** No irritant effect.

**on the eye:** No irritating effect.

**Sensitization:** No sensitizing effects known.

##### Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

##### Carcinogenic categories

##### IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

##### NTP (National Toxicology Program)

None of the ingredients is listed.

##### OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

#### Toxicity

##### Aquatic toxicity:

EC50	> 5 mg/l (bacteria)
------	---------------------

	250-350 mg/l (fish)
--	---------------------

**Persistence and degradability** No further relevant information available.

**Other information:** The product is easily biodegradable.

##### Behavior in environmental systems:

**Bioaccumulative potential** No further relevant information available.

**Mobility in soil** No further relevant information available.

##### Additional ecological information:

##### General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

**Results of PBT and vPvB assessment** Not applicable.

**PBT:** Not applicable.

**vPvB:** Not applicable.

**Other adverse effects** No further relevant information available.

### 13 Disposal considerations

#### Waste treatment methods

Waste disposal according EC-regulations 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

**Recommendation:** Must be specially treated adhering to official regulations.

(Contd. on page 6)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2015

Version 4

Reviewed on 05/30/2015

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

(Contd. of page 5)

**Uncleaned packagings:****Recommendation:**

Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

## 14 Transport information

**UN-Number**

DOT, ADR, ADN, IMDG, IATA

Void

**UN proper shipping name**

DOT, ADR, ADN, IMDG, IATA

Void

**Transport hazard class(es)**DOT, ADR, ADN, IMDG, IATA  
Class

Void

**Packing group**

DOT, ADR, IMDG, IATA

Void

**Environmental hazards:****Marine pollutant:**

No

**Special precautions for user**

Not applicable.

**Transport in bulk according to Annex II of  
MARPOL73/78 and the IBC Code**

Not applicable.

**UN "Model Regulation":**

UN-, -

## 15 Regulatory information

**Safety, health and environmental regulations/legislation specific for the substance or mixture****Sara****Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

**Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

**TSCA (Toxic Substances Control Act):**

112-35-6 2-(2-(2-methoxyethoxy)ethoxy)ethanol

15520-05-5 2,2'-(Octylimino)bisethanol

111-46-6 2,2'-oxybisethanol

68442-68-2 Benzenamine, N-phenyl-, styrenated

29385-43-1 methyl-1H-benzotriazole

23783-42-8 2-(2-methoxyethoxy)ethanol

4314-14-1 Fat Yellow 3G

68439-46-3 Alcohol ethoxylate (C9-C11, 6 EO)

**Proposition 65****Chemicals known to cause cancer:**

None of the ingredients is listed.

**Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 7)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/05/2015

Version 4

Reviewed on 05/30/2015

Trade name: Original ATE Brake Fluid TYP 200 (DOT 4)

(Contd. of page 6)

**Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

**Carcinogenicity categories****EPA (Environmental Protection Agency)**

None of the ingredients is listed.

**TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

**NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Recommended restriction of use**

Reserved for industrial and professional use.

For industrial purposes only.

**Date of preparation / last revision** 06/05/2015 / 3**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

**Sources**\* **Data compared to the previous version altered.**

US